

# Quality You Can Trust

## FROM THE LEADER IN BETWEEN-COAT FLOOR SANDING

For more than 20 years, floor sanding professionals have preferred Norton SandDollar discs for surface prep between coats of finish. With a unique patented design, these discs allow you to create a smooth layer and a flawless floor.



You can rely on these benefits:



### Fine scratch pattern

consistent, even abrasion with no swirl marks



### Long life

approximately 1500 sf/pad, discs can even be vacuumed or rinsed and re-used



### Anti-loading

cut-outs on the pad optimize dust extraction



### Color-fast

dye colors won't wear off or contaminate the surface



### Ideal adhesion

aluminum oxide grain bonded to the foam backing creates the perfect surface for accepting the next coat





### Specialized Uses

Expressly designed for **sports floors**, the 20" pad eliminates the risk of cutting through the finish on marking lines and logos. Available in three grits:

**Coarse / Blue**  
for surface prep for recoating

**Medium / Red**  
for between-coats abrading of oil modified finishes

**Fine / Yellow**  
for waterbase finishes

### Ordering Information\*

PART #	COLOR	GRIT	PACK QTY
<b>16" Diameter</b>			
78072775500	Blue	60	5
78072775501	Red	100	5
78072775502	Yellow	120	5
78072775503	Green	180	5
<b>16" Diameter – Bulk</b>			
78072775504 <i>NS</i>	Blue	60	50
78072775505 <i>NS</i>	Red	100	50
78072775506 <i>NS</i>	Yellow	120	50
<b>20" Diameter</b>			
78072775507	Blue	60	5
78072775508	Red	100	5
<b>20" Diameter – Bulk</b>			
77696099012 <i>NS</i>	Blue	60	50
77696099013 <i>NS</i>	Red	100	50
66254446105 <i>NS</i>	Yellow	120	50

*NS = Non-Stock > MOQ = 500*

\* Note: New part numbers as of 01/15/25

### Cross Reference Chart

NORTON SANDDOLLAR	SCREEN	MAROON PAD & PSA SHEET TOLLS
<b>BLUE (COARSE)</b>	100-120 grit	150 <sup>†</sup> grit PSA
<b>RED (MEDIUM)</b>	120-150 grit	150 grit PSA
<b>YELLOW (FINE)</b>	150-180 grit	180 grit PSA
<b>GREEN (VERY FINE)</b>	220 grit	240 grit PSA

<sup>†</sup> Can be used in place of 150 grit PSA to abrade rough sealer coats and finish coats without cutting through the finish or leaving swirl marks

### Application Reference Chart

APPLICATION	BLUE (COARSE)	RED (MEDIUM)	YELLOW (FINE)	GREEN (VERY FINE)
<b>Surface Prep</b>				
Recoat Heavy Wear	☼			
Recoat Light Wear	☼	☼		
<b>Sealer Coat</b>				
Oil Modified / Acid Cure	☼	☼		
Waterbase		☼	☼	
<b>Finish Coat</b>				
Oil Modified/Acid Cure		☼	☼	
Waterbase		☼	☼	☼ <sup>†</sup>
<b>Final Sanding</b>				
Bare Wood	☼			

<sup>†</sup> For light abrading before final coat of waterbase