Product Datasheet

PALLMANN®

WOOD FLOOR FILLER

PALL-X FILLER

Water-based fiber-reinforced wood filler compound for wood floors

PRODUCT DESCRIPTION:

Waterbourne wood filler with patented fiber-reinforced technology to reduce shrinkage. Suitable for most sandable wood flooring species.

SUITABLE FOR:

- Solid strip, plank, engineered and parquet flooring, uses sanding dust to create the perfect color match
- Radiant heat floor systems

NOTE:

BEFORE USING, READ ALL DIRECTIONS AND THE SAFETY DATA SHEET (SDS). FOR PROFESSIONAL USE ONLY.

This product meets or exceeds all state and federal clean air quality standards and reflects our commitment to personal health, indoor air quality and the environment.

If technical advice is needed, call the PALLMANN® division of Uzin Utz North America (1-866-505-4810) before using the product.

TECHNICAL DATA:

Packaging:	1 U.S. plastic gallon (3.78 Liters)
Shelf life:	Minimum 18 months*
Color:	Yellow when wet, color-matched to species when dry
Mixing ratio:	Blend to a paste consistency that can be trowel applied
Consumption per coat:	Approx. 400 sq. ft. per gallon, depending on floor condition
Working climate:	65 – 75 °F (18 – 25 °C) for optimum performance; Store between 50 – 70 °F (10 – 20 °C), Keep from freezing
Ready for sanding:	20 – 25 minutes
VOC	< 130 g/L

At 70 °F (21 °C) and 65% relative humidity.

FEATURES – BENEFITS:

- Fiber-reinforced – Reduces shrinkage
- Mix with sanding dust – Perfect color match
- No-clog formula – Won't load on abrasives
- Fast-drying – Less down time
- Adjustable viscosity – Mix to desired consistency

PALLMANN | A brand of UZIN UTZ
Uzin Utz North America, Inc. | toll free 866-505-4810 | 720-374-4810 | 14509 E. 33rd Place, Unit G, Aurora, CO 80011 | pallmann.us@uzin-utz.com | us.pallmann.net

APPLICATION:

Shake product well prior to mixing with 80 – 100 grit edger or buffer sanding dust. Pour the PALL-X FILLER into a 'crater' of sanding dust on the floor to be filled. Using a stainless steel trowel (Item #12506), blend the liquid with the dust to achieve a trowelable paste consistency. Trowel apply to the floor, filling all joints and gaps.

NOTE:
From time to time it will be necessary to add more PALL-X FILLER to the mix on the floor to maintain a paste-like consistency. PALL-X FILLER may also be mixed with sanding dust in a bucket prior to trowel application.

IMPORTANT:
The filling application should be made before the final cut with the belt or drum sander. The floor can normally be sanded 20 to 25 minutes after filling. High humidity and / or low temperature conditions may extend the dry time while increased ventilation and airflow may reduce dry time. PALL-X FILLER must be removed with a belt sander or the PALLMANN SPIDER. Do not attempt to remove PALL-X FILLER with only a single drive plate rotary buffer. To ensure proper color match, test filler, stain and finish in an inconspicuous area.

ADDITIONAL NOTES:

Clean Up
Tools and applicators should be cleaned with water

Storage
Minimum 12 months in original packaging when stored under normal conditions (50 – 70 °F / 10 – 20 °C). Tightly reseal opened containers. Keep from freezing

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Do not handle until all safety instructions have been read and understood. Safety Data Sheet (SDS) is available at www.pallmann.us.

DISPOSAL:

Dispose of the material in accordance with applicable laws and regulations. Avoid product to get in contact with soil, waterways, drains, or sewers. Empty containers or liners may retain product residues.

INDOOR AIR QUALITY INFORMATION

VOC content: < 130 g/L, compliant with SCAQMD Rule 1113

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgment and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer. The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our homepage at us.pallmann.net | 01/2025